

TECHNICAL DATA SHEET

GEO40™ SOL-1430Na

Geo40™ SOL-1430Na is a sustainable geothermal water derived colloidal silica stabilized with sodium. An alkaline dispersion of 13.5 nm colloidal silica at 30 % SiO₂ concentration in water. The particles are negatively charged and have a high specific surface area.

The product can be used in a wide variety of applications such as metals and refractories, paper and textiles treatment, coatings and inks, or other applications where a small particle size colloidal silica is required.

PROPERTIES

Tests	Range	Units
Particle size	12.5 to 14.5	nm
Silica (as SiO ₂)	29.0 to 31.0	w / w%
pH	8.8 to 9.8	pH
Density	1.193 to 1.209	kg / L
Conductivity	1.0 to 4.0	mS / cm
Surface area	188 to 218	m ² / g
Free Alkalinity (as Na ₂ O)	0.1 to 0.4	w / w%
Viscosity	Less than 12.0	cP
Accelerated Life Test	Pass	80 °C / 7 days
Visual Appearance	Clear to Opaque	
Warranty Period	12	months

TO ORDER MATERIAL, OR FIND OUT MORE

Please contact: SALES@GEO40.COM

This Technical Data Sheet has been prepared by Geo40™ Limited for information purposes only. While Geo40™ has used all reasonable care to ensure that the information is free from error, Geo40™ does not warrant its accuracy, adequacy or completeness or that Geo40™ SOL-1430Na will be suitable for your intended use. The only warranties provided are those set out in Geo40™ Terms and Conditions of Trade. To the extent permitted by law, all other warranties relating to this information or Geo40™ SOL-1430Na (whether express, implied or statutory) are excluded. GEO40™ is a trademark of Geo40™ Limited. © 2019 Geo40™ Limited.