

TECHNICAL DATA SHEET

GEO40™ SOL-1030NH₃ (COMMERCIAL SAMPLES ONLY)

Geo40™ SOL-1030NH₃ is a sustainable geothermal water derived colloidal silica stabilized with sodium and ammonia. An alkaline dispersion of 10 nm colloidal silica at 30 % SiO₂ concentration in water. The particles are negatively charged and have a high specific surface area. Ammonia is added to increase the pH and stability while maintaining moderate sodium levels.

The product can be used in a wide variety of applications such as metals and refractories, paper and textiles treatment, coatings and inks, or other applications where a small particle size colloidal silica is required, and low sodium is desired.

TYPICAL PROPERTIES

Tests	Target Value	Units
Particle size	10.0	nm
Silica (as SiO ₂)	30.0	w / w%
pH	9.7	pH
Density	1.201	kg/L
Conductivity	4.5	mS/cm
Surface area	276	m ² /g
Free Alkalinity (as Na ₂ O)	Less than 0.08	w / w%
Viscosity	Less than 15.0	cP
Accelerated Life Test	Pass	80°C / 7 days
Visual Appearance	Clear to Opaque	

TO ORDER MATERIAL, OR FIND OUT MORE

Please contact: SALES@GEO40.COM

This Technical Data Sheet has been prepared by Geo40™ Limited for information purposes only. While Geo40™ has used all reasonable care to ensure that the information is free from error, Geo40™ does not warrant its accuracy, adequacy or completeness or that Geo40™ SOL-1030NH₃ will be suitable for your intended use. The only warranties provided are those set out in Geo40™ Terms and Conditions of Trade. To the extent permitted by law, all other warranties relating to this information or Geo40™ SOL-1030NH₃ (whether express, implied or statutory) are excluded. GEO40™ is a trademark of Geo40™ Limited. © 2019 Geo40™ Limited.